

MESSMATE



MESSMATE

MESSMATE IS A HIGHLY VERSATILE PRODUCT SUITABLE FOR A VARIETY OF COMMERCIAL AND RESIDENTIAL APPLICATIONS.

Ranging in colour from pale to light brown, this timber offers both character and resilience whilst providing an impressive addition to any project.

Ideal for commercial applications where a light and airy ambience is required. Messmate is widely used within the residential building industry across various applications including cladding, flooring and bespoke joinery items.

Recognised for its unique grain and rich patina. Messmate adorns many notable projects. With an incredible colour palette and ability to charm any space, Messmate is available to order now.



COMMON NAME	Messmate
LOOK & FEATURES	Medium and even texture with frequent gum veins.
BOTANICAL NAME	Eucalyptus Obliqua
COLOUR	Pale through to light brown.
COMMON USES	A wide range of internal applications including cladding, flooring and bespoke joinery.

PROPERTIES

DENSITY (KG/M3)	
GD	1080
ADD	750
HARDNESS KN (JANKA)	
Green	5.3
Dry	7.1
DURABILITY CLASS	3
STRENGTH GROUP	S3/SD3
JOINT GROUP	J3/JD3
SHRINKAGE	
Radial % (approx.)	> 5.0
Tangential % (approx)	11.3
STRUCTURAL GRADES	
Unseasoned	F11/F14/F17
Seasoned	F22/F27+
TOUGHNESS (NM)	
Green	Medium
Dry	Medium
EARLY FIRE HAZARD INDICES	
Ignitability	13
Spread of Flame	5
Smoke Development	3
TERMITE RESISTANT	NR
LYCTID SUSCEPTIBLE SAPWOOD	Yes